

# 6000 SERIES



No. **1** Tractor  
Company  
in the World \*



DEMING PRIZE  
2003



JAPAN QUALITY MEDAL  
2007

**Mahindra**  
Tractors

\*MSM Ltd. is the largest tractor company in the world, by volume



## TOUGH. EFFICIENT. EFFORTLESS.

The New Generation Mahindra 6000 series tractors, are designed to perform multiple tasks, passing through the rigors of works with ease.

Loaded with impressive standard features, the complete equipment package offers a high performance 4 Cylinder, Direct Injection, Water cooled, Turbo Charged engine, easy shift synchromesh transmission with Synchro shuttle and big lift capacity.

Offering a range of tractor HP from 57 to 75 HP and with 4WD, there is always a model to meet your needs.

### Key Features:

- Fuel efficient 4 cylinder engines
- 15F / 15R Synchromesh Transmission with Synchro Shuttle
- Independent 540 and 540 E PTO

- Best in class operating weight for more built in traction, stability and control for a safer operating environment.
- Clear-view instrument cluster and easy to use ergonomic controls
- Best in class 3-point lift capacities

### Ideal For:

- Agriculture
- Hay
- Material Handling

- Livestock
- Dairy

## NEW GENERATION, TECHNOLOGICALLY ADVANCED ENGINE

The 6000 Series tractors are powered by a naturally aspirated, 4 cylinder direct injection diesel engine. They are designed to ensure a flat torque curve and maximized torque levels, FROM 213 Nm TO 305 Nm, ensuring maximum productivity in both PTO and draft applications. Excellent Torque reserve up to 25% gives plenty of lugging ability reducing the need for frequent gear shifts during tough conditions.

## HEAVY DUTY TRANSMISSION

The standard 15F+15R, synchromesh heavy duty transmissions are extremely reliable and easy to-use. They incorporate very wide gears providing great strength for the high torque loads being transmitted. The high nos of speed options allows to perform a broad range of farming applications successfully.

The Power shuttle makes shifting between forward and reverse smooth and quick. It eliminates the need to depress the clutch every time you change directions, thereby ensuring maximum productivity during intensive headland operations.





## POWERFUL HYDRAULICS AND STURDY 3-POINT LINKAGE.

Heavy and sturdy 3 point linkage is employed to ensure stability and safety. The lower links provide fast and simple attachment of rear mounted implements.

The live powerful hydraulics boasts a maximum lift capacity of 2200 kg for 6060 model & 2600 kg for 6075 model, to handle the heaviest of implements.

Two double acting remote control valves are standard.



## HEAVY DUTY FRONT AXLE

High reliability in loader and field operations is ensured by using the front axle which is designed for higher class tractors.

In the 4WD models, the epicyclic reduction offers high dynamic load carrying capacity and is designed for maximum performance in loader and field operations. The responsive hydrostatic steering has a tight steering angle, for effortless maneuvering even in confined areas.

## COMFORTABLE WORK ENVIRONMENT

The fully flat operator deck with side shift gear levers, suspended brake and clutch pedal provides lots of legroom and a spacious work area.





# TRACTOR SPECIFICATIONS

TRACTOR	6060 4WD	6075 4WD
<b>ENGINE</b>		
Type	Four Stroke, Direct Injection, Turbocharged, Water Cooled Diesel Engine	Four Stroke, Direct Injection, Turbocharged, Water Cooled Diesel Engine
Cylinders	4	4
Engine HP @ rpm	57 HP @ 2100	75 HP @ 2100
Displacement cubic (cc)	3533	3822
<b>ELECTRICAL</b>		
Battery Capacity	12V, 88AH	12V, 100AH
Alternator	12V, 45A	12V, 55A
<b>CLUTCH</b>		
Type	Dual Diaphragm Type	Dual Diaphragm Type
<b>TRANSMISSION</b>		
Type	Mechanical Partial Synshromesh	Mechanical Partial Synshromesh
Number of Gears / Speeds	15 Forward, 15 Reverse with Synchro Shuttle	15 Forward, 15 Reverse (F/R Shuttle)
<b>STEERING</b>		
Type	Hydrostatic Power Steering	Hydrostatic Power Steering
<b>BRAKES</b>		
Type	Mechanical, Oil Immersed, Multi Disc Brakes	Mechanical, Oil Immersed, Multi Disc Brakes
<b>HYDRAULIC SYSTEM</b>		
Type	Live Hydraulics with draft & position control	Live Hydraulics with draft & position control
3-Point Linkage	Cat II 3 Point linkage with check chain	Cat II 3 Point linkage with stabilizer bar
Lift Capacity (Kg.)	2200	2600
Rear Auxiliary Remote Valves	Double spool	Double spool
<b>PTO</b>		
Type	Rear mounted 8 spline 2 speed PTO	3 Speed SLIPTO
PTO RPM (Engine rpm)	568 @ 2100	540 @ 1993/ 540 @ 1470 / Rev PTO
PTO HP	49.5	66
<b>OPERATING WEIGHT</b>		
Total (Kg.)	3170	3370
<b>DIMENSIONS with Ag Tires</b>		
Overall Length (mm)	3695	3750
Overall Width (mm)	1990	1990
<b>TIRES Sizes and Options</b>		
Ag (Front / Rear)	9.5 X 24 16.9 X 28	12.4 X 24 18.4 X 30