

NEW GENERATION POWERFUL EFFORTLESS



Durability

- Best in Class 4-Yr Warranty or 3,000hrs.
- Free 2-Yr Maintenance Kits
- Strong Design to withstand long hours of usage

6060, 6065 and 6075 3 Models



Versatility

- Best in Class Driving Efficiency via 15x15 F/R Synchro Shuttle
- Best Choice of Tractor for tough soil and tough working conditions
- Muscular Loads Design, ideally suit with multi-utility purpose
- Draft Control equipped across the series



High Performance

- Best in Class Lift Capacity, up to 2,700kg (Model 6060 and 6065) and 2,900kg (Model 6075)
- Best in Class Engine Torque ensures Best in Class Pulling Power
- Best in Class Smooth Driving Experience, finer speed - 15x15 F/R Synchro Shuttle
- On the go PTO (Independent PTO), avoid loss of power



Cost Efficiency

- Powerful DI Engine - Saving 10%* more fuel efficient (with greater depth of operations)



Smart Features

- Stay Connected with next gen apps. (Optional - with DiGiSense)

6060, 6065 and 6075 Models

TRACTOR	6060 4WD	6065 4WD	6075 4WD
ENGINE			
Type	Four Stroke, Direct Injection, Water Cooled, Diesel Engine	Four Stroke, Direct Injection, Water Cooled, Diesel Engine	Four Stroke, Direct Injection, Turbocharged, Water Cooled, Diesel Engine
Cylinders	4	4	4
Engine HP @ rpm	57 @ 2100	65 @ 2100	75 @ 2100
Displacement cubic (cc)	3,532	3,822	3,822
Max. Torque (Nm)	213	250	306
ELECTRICAL			
Battery Capacity	12V, 100Ah	12V, 110Ah	12V, 100Ah
Alternator	12V, 45A	12V, 55A	12V, 55A
CLUTCH			
Type	Dual Clutch	Dual Clutch	Dual Clutch
TRANSMISSION			
Type	Partial Synchromesh	Partial Synchromesh	Partial Synchromesh
Number of Gears	15 Forward, 15 Reverse with Forward-Reverse shuttle	15 Forward, 15 Reverse with Forward-Reverse shuttle	15 Forward, 15 Reverse with Forward-Reverse shuttle
STEERING			
Type	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
BRAKES			
Type	Oil Immersed Brake	Oil Immersed Brake	Oil Immersed Brake
HYDRAULIC SYSTEM			
Type	Live Hydraulic with Position & Draft Control	Live Hydraulic with Position & Draft Control	Live Hydraulic with Position & Draft Control
3-Point Linkage	Cat II with check chain	Cat II with check chain	Cat II with stabilizer bar and telescoping lower link
Lift Capacity at Hitch Point (kg)	2,700	2,700	2,900
Rear Auxiliary Remote Valves/ Tipping Trailer Pipe	Double Spool Aux. Valve	Double Spool Aux. Valve	Double Spool Aux. Valve
PTO			
Type	Independent PTO	Independent PTO	Independent PTO
PTO RPM	540, 540E	540, 540E	540, 540E and Reverse
PTO HP	50	57	66
OPERATING WEIGHT			
Total (kg)	3,159	3,326	3,445
DIMENSIONS with Ag Tires			
Overall Length (mm)	3,705	4,050	4,052
Overall Width (mm)	1,990	2,000	2,000
TIRES Sizes and Options			
Ag (Front)	9.5 x 24	11.2 x 24	12.4 x 24
Ag (Rear)	16.9 x 28	16.9 x 30	18.4 x 30

